

13/18V 0/22K SWITCH



FEATURES:

- ★ Zinc die-cast housing, nickel-plated.
- ★ Wide switching range, compatible with more types of satellite receiver.
- ★ Select one of two satellite signals through 13\18V.
- ★ Power supplied from receiver.
- ★ Use one cable to transmit control signal and satellite signal at the same time.
- ★ High quality component and professional design.

SPECIFICATION:

Item	Unit	TK21V
Frequency Range	MHz	950-2400
Insertion Loss	dB	≤3
Isolation	dB	≥20
Return Loss	dB	≥10
Normal Working Voltage	VDC	12--20
DC Power Consumption	mA	10
DC Max Power Passing	mA	800



FEATURES:

- ★ Zinc die-cast housing, nickel-plated.
- ★ Wide switching range, compatible with more types of satellite receiver.
- ★ Select one of two satellite signals through 0\22K signal.
- ★ Power supplied from receiver.
- ★ Use one cable to transmit control signal and satellite signal at the same time.
- ★ High quality component and professional design.

SPECIFICATION:

Item	Unit	TK21K
Frequency Range	MHz	950-2400
Insertion Loss	dB	≤3
Isolation	dB	≥20
Return Loss	dB	≥10
Normal Working Voltage	VDC	12--20
DC Power Consumption	mA	10
DC Max Power Passing	mA	800